

4 WAY 60x60 CASSETTE INVERTER



Specially designed for offices, retail and restaurant applications, this cassette fits perfectly into 60x60 or 70x70 ceiling grids.

Featuring the best efficiency in its category (heating and cooling up to -10°C, this new cassette in 9 and 12 kW versions can also be connected to KNX, Modbus, EnOcean interfaces for easy integration with your BMS systems. Interfaces have dry contacts (ON/OFF, error message) to enable easy integration.

With the new IntesisHome interface, you can also control the cassette from your smartphone and internet very easily!

Fit Panasonic's Cassette Type, and start to save all year round!

Technical focus

- Cassettes can be controlled by IntesisHome, KNX, EnOcean and Modbus
- This units can be installed on R22 pipings
- Designed for easy installation in the standard European 60x60 ceiling grid
- Operation down to -10°C in cooling and heating modes
- Piping length up to 30 m
- Maximum elevation difference up to 20 m
- Ultra compact outdoor units for easy installation
- High pressure selector in case of high ceilings (higher than 2.7 m)
- Drain pump included (maximum 750 mm high)
- Air fresh entry available on the cassette

| KIT | | KIT-E9-PB4EA | KIT-E12-PB4EA | KIT-E18-RB4EA | KIT-E21-RB4EA |
|--|------------------------------------|-------------------|-----------------------------|----------------------------------|-----------------------------|
| Cooling capacity | Nominal (Min - Max) | kW | 2.50 (0.85 - 3.00) | 3.40 (0.85 - 4.00) | 5.00 (0.90 - 5.80) |
| EER ¹⁾ | Nominal (Min - Max) | W/W | 4.55 (3.54 - 4.05) A | 3.82 (3.54 - 3.33) A | 3.13 (3.53 - 2.97) B |
| SEER | | W/W | 5.80 h | 5.60 h | 5.80 h |
| Pdesign (cooling) | | kW | 2.50 | 3.40 | 5.00 |
| Power input cooling | Nominal (Min - Max) | kW | 0.550 (0.240 - 0.740) | 0.890 (0.240 - 1.200) | 1.600 (0.255 - 1.950) |
| Annual electricity consumption (cooling) ²⁾ | kWh/a | | 151 | 213 | 302 |
| Heating capacity | Nominal (Min - Max) | kW | 3.20 (0.85 - 4.80) | 4.50 (0.85 - 5.60) | 5.60 (0.90 - 7.10) |
| Heating capacity at -7°C | Nominal | kW | 2.60 | 3.00 | |
| COP ¹⁾ | Nominal (Min - Max) | W/W | 4.00 (3.70 - 3.56) A | 3.17 (3.7 - 2.80) D | 3.01 (3.46 - 2.92) D |
| SCOP | Nominal | W/W | 4.00 h | 3.80 a | 4.10 h |
| Pdesign at -10°C | | kW | 2.70 | 3.00 | 3.80 |
| Power input heating | Nominal (Min - Max) | kW | 0.800 (0.230 - 1.350) | 1.420 (0.230 - 2.000) | 1.860 (0.260 - 2.430) |
| Annual electricity consumption (heating) ²⁾ | kWh/a | | 945 | 1,105 | 1,298 |
| Indoor Unit | | | CS-E9PB4EA | CS-E12PB4EA | CS-E18RB4EAW |
| Power source | | V | | 230 | |
| Recommended fuse | | A | | 16 | |
| Connection | | mm ² | | 4 x 1.5 to 2.5 | |
| Air volume | Cooling / Heating | m ³ /h | 630 / 648 | 630 / 648 | 690 / 708 |
| Moisture removal volume | | l/h | 1.5 | 2.3 | 2.8 |
| Sound pressure level ³⁾ | Cooling - Heating (Hi / Lo / S-Lo) | dB(A) | 34 / 26 / 23 - 35 / 28 / 25 | 37 / 28 / 25 - 38 / 29 / 26 | 42 / 33 / 30 - 43 / 34 / 31 |
| Dimensions (H x W x D) | Indoor / Panel | mm | | 260 x 575 x 575 / 51 x 700 x 700 | |
| Net weight | Indoor / Panel | kg | | 18 / 2.5 | |
| Outdoor Unit | | | CU-E9PB4EA | CU-E12PB4EA | CU-E18RBEA |
| Sound pressure level ³⁾ | Cooling / Heating (Hi) | dB(A) | 45 / 46 | 45 / 47 | 47 / 48 |
| Dimensions ⁴⁾ / Net weight | H x W x D | mm / kg | 622 x 824 x 299 / 36 | 695 x 875 x 320 / 45 | 695 x 875 x 320 / 47 |
| Piping connections | Liquid / Gas pipe | Inch | | 1/4 / 3/8 | 1/4 / 1/2 |
| Piping length range / Elevation difference (in/out) | | m | | 3 ~ 20 / 15 | 3 ~ 30 / 20 |
| Pipe length for additional gas / Additional gas amount | | m / g/m | | 10 / 20 | |
| Operating range | Cooling - Heating (Min / Max) | °C | | -10 ~ +43 / -10 ~ +24 | |

| Accessories | Accessories |
|---------------|---|
| PAW-AC-WIFI-1 | Full bidirectional Wifi interface for Internet control |
| PAW-IR-WIFI-1 | IR Wifi interface for Internet control |
| | CZ-RD52CP |
| | Wired remote control for Cassette and Hide Away |
| | CZ-CAPRA1 |
| | H Generation interface to ECOi control integration (available in June 2016) |

1) EER and COP classification is at 230 V in accordance with EU directive 2002/31/EC. 2) The annual energy consumption is calculated in accordance with the ErP directive. 3) The Sound pressure level of the units shows the value measured of a position 1 metre in front of the main body and 1.5m below the ceiling in the centre of the unit. The sound pressure is measured in accordance with Eurovent 6/C/006-97 specification. 4) Add 70mm for piping port.



SEER and SCOP: For KIT-E9-PB4EA. SUPER QUIET: For KIT-E9-PB4EA and KIT-E12-PB4EA. INTERNET CONTROL and INTEGRATION P-LINE: Optional. 5 YEARS COMPRESSOR WARRANTY: Only for PRO Partners.